Mix Pump U3-02





The U3 pump is the simplest pump available. No disassembly required for cleaning. The U3 pump has a capacity of 36 gallons per hour of standard soft serve or shake mix with an adjustable overrun. For use with all remote soft serve and shake freezers.

Dimensions: 10-1/2"D x 9-3/4"W x 8-1/2"H

weight: 27 lbs.

Electrical: 1 phase,115 VAC, 60Hz.

1.6 running amps

Cord and plug attached

International Option: 1 phase, 220-240 VAC, 50Hz

Warranty: One year parts only

Excludes wear items and labor

Includes: Spare parts kit, wall mounting bracket,

and suction tubing

Continuous research leads to ongoing product improvements; therefore, these specifications are subject to change without notice.

Distributed by:



stoeltingfoodservice.com

Stoelting Foodservice Equipment 502 Highway 67 • Kiel, WI 53042-1600 920-894-2293 • 800-558-5807 Customer/Technical Service: 888-429-5920

E-mail: foodservice@stoelting.com

CUL US (NSF.)

and/or Recognized by:

Certified, Listed

ISO 9001:2008 Registered STMF-139 4/14 **Mix Pump** 219-02





The 219 pump has a capacity of 45 gallons per hour of standard soft serve or shake mix with an adjustable overrun. For use with all Stoelting manufactured freezers. Includes a built-in pressure relief valve to prevent excessive pressure build-up in the freezing cylinder or mix line, and air-controlled pressure switch and overload protection. Factory set pressure.

Dimensions: 8-3/4"D x 15"W x 17-1/2"H

weight: 33 lbs.

Electrical: 1 phase, 115 VAC, 60 Hz.

0.7 running amps

Cord and plug attached

Warranty: One year parts only

Excludes wear items and labor

Includes: Spare parts kit, wall mounting bracket,

and suction tubing

Continuous research leads to ongoing product improvements; therefore, these specifications are subject to change without notice.

Distributed by:



stoeltingfoodservice.com

Stoelting Foodservice Equipment 502 Highway 67 • Kiel, WI 53042-1600 920-894-2293 • 800-558-5807 Customer/Technical Service: 888-429-5920

E-mail: foodservice@stoelting.com



ISO 9001:2008 Registered STMF-139 4/14